

## P9000 GOLD

PREMIUM  
PERFORMANCE  
FULLY SYNTHETIC  
ENGINE OIL WITH ESTER

**MaxPro1 P9000 Gold** premium fully synthetic engine oil is developed according to the latest friction-reducing technology. It is formulated with synthetic base oils, ester and a well-balanced additive package, to provide high levels of fuel efficiency and deposit protection under severe service conditions.

Excellent wear protection and friction reduction across a wide range of operating conditions. Meets the latest API SN standard for gasoline engines.

### APPLICATIONS

**MaxPro1 P9000 Gold** is suitable for use in passenger cars and light truck engines requiring low viscosity, ILSAC GF-5 and API SN performance lubricants under all operating conditions.

**MaxPro1 P9000 Gold SAE 0W-20** is NOT recommended for use in diesel engined vehicles or in motorcycles with wet clutches.

### FEATURES AND BENEFITS

- Optimising energy efficiency and fuel economy
- Excellent high temperature deposit protection for pistons and turbochargers
- More stringent sludge control
- Enhanced emission control system compatibility and seal compatibility
- Protection of engines operating on ethanol-containing fuels up to E85



## P9000 GOLD

PREMIUM  
PERFORMANCE  
FULLY SYNTHETIC  
ENGINE OIL WITH ESTER

### PERFORMANCE LEVEL

It meets or exceeds the performance requirements of:

- API SN
- ILSAC GF-5 (SAE 0W-20 & SAE 0W-30 Only)

### TYPICAL PHYSICAL CHARACTERISTICS

SAE Grade			SAE 0W-20	SAE 0W-30	SAE 0W-40
Product Code			1108	1109	1110
Test	Unit of Measure	Method	Typical Value	Typical Value	Typical Value
Density @ 15°C	kg/l	D4052	0.845	0.842	0.845
Colour ASTM	-	D1500	< 2.5	< 2.5	< 2.5
Appearance	-	Visual	Clear	Clear	Clear
Viscosity @ 100°C	cSt	ASTM D445	8.3	11.0	14.2
Viscosity @ 40°C	cSt	ASTM D445	45.1	62.3	89.2
Viscosity Index	-	D2270	161	170	165
CCS @ -35°C	cP	D5293	4,605	5,600	6,010
Flash Point	°C	ASTM D92	230	232	236
Pour Point	°C	ASTM D97	-42	-45	-49

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

### Available Size & Part Number

	1L	4L
P9000 Gold SAE 0W-20	1108-01	1108-04
P9000 Gold SAE 0W-30	1109-01	1109-04
P9000 Gold SAE 0W-40	1110-01	1110-04

