

P5000

PREMIUM
PERFORMANCE
GASOLINE ENGINE OIL

MaxPro1 P5000 premium quality automotive engine oils are formulated to provide extra protection against the harmful effects of stop-and-go driving and extreme temperature operations. All grades are formulated with high quality base stocks and robust additive packages to provide excellent engine protection under the most severe operating conditions, even with long drain intervals.

APPLICATIONS

MaxPro1 P5000 oils are universal engine lubricants, which meet the strict ACEA A3 and B3 specifications required by many late model European and Japanese Petrol and Diesel engines. Suitable for use in all petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.

FEATURES AND BENEFITS

- Excellent anti wear protection
- Protection against thermal breakdown
- Clean engines and positive crankcase ventilation systems resulting in minimal deposits under heavy load and stop-and-go driving conditions.
- Meets or exceeds warranty requirements of car and light truck manufacturers relying on an API SM, SL or SJ service category engine oil.

PERFORMANCE LEVEL

It meets the performance requirements of:

- API SM/CF
- ACEA A3 / B3
- VW 501 / 505



Revision 23/09/15 Superseding
issue of

TYPICAL PHYSICAL CHARACTERISTICS

SAE grade	Test Method	15W-40	20W-50
Product Code		1121	1122
Appearance	VISUAL	B & C	B & C
ASTM Colour	ASTM D1500	L2.5	L3.0
Density@ 15°C , kg/l	ASTM D1298	0.859	0.864
Viscosity, kinematic			
at 40°C , cSt	ASTM D445	108.2	175
at 100°C , cSt	ASTM D445	14.1	18.8
Viscosity Index	ASTM D2270	132	121
Flash point, COC , °C	ASTM D92	>220	>220
Pour point , °C	ASTM D97	-30	-24
TBN , mg KOH/g	ASTM D2890	7	7
CCS @ -20°C , cP	ASTM D5638	<7,000	-
CCS @ -15°C , cP	ASTM D5638	-	<9.500

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

Available Size & Part Number

	4L	5L	200L
P5000 SAE 15W-40	1121-04		1121-200
P5000 SAE 20W-50	1122-04		1122-200



Revision 23/09/15 Superseding
issue of