

**MaxPro1 P2000** is a robust multi-grade engine oil formulated for passenger cars, vans and light trucks with petrol and naturally aspirated diesel engines. Being a SAE 20W-50 viscosity oil it gives good high temperature performance by providing a thicker oil film on bearing surfaces as well as better sealing of piston rings. It exceeds API Service Classification SG/CD.

---

### APPLICATIONS

**MaxPro1 P2000** Premium Engine Oil 20W-50 is recommended for older naturally aspirated petrol and diesel engines of passenger cars, mini buses, taxis, light commercial vehicles and equipment involved in start/stop operations with short service intervals. It can also be used as a non-extreme pressure gear lubricant where engine oils of the same quality and viscosity range are recommended. Always consult the manufacturer's operating manual to confirm the suitability of the lubricant for a particular vehicle.

---

### FEATURES AND BENEFITS

- Excellent protection against wear and corrosion.
- Keeps engines clean.
- Maintains optimum viscosity at all temperatures.
- Smooth engine operation.
- Lowers engine operating temperature & resists oxidation
- Improves fuel mileage
- Lengthens oil changes interval



Revision 23/09/15 Superseding  
issue of

### PERFORMANCE LEVEL

It meets the performance requirements of:

- API SG/CD
- MIL-L-2104D

### TYPICAL PHYSICAL CHARACTERISTICS

SAE grade	Test Method	20W-50
Product Code		<b>1125</b>
Density at 15°C, Kg/L	ASTM D1298	0.89
Viscosity at 40°C, cSt	ASTM D445	170
Viscosity at 100°C, cSt	ASTM D445	18.5
Viscosity Index	ASTM D2270	115
Flash Point, COC, °C	ASTM D92	240
Pour Point, °C	ASTM D97	-15
TBN, mgm KOH/gm	ASTM D2896	8.3

The information provided is to our best knowledge, true & accurate, Subjected to change without notification due to continual product research and development.

### Available Size & Part Number

	4L	18L	200L
<b>P2000 SAE 20W-50</b>	<b>1125-04</b>	<b>1125-18</b>	<b>1125-200</b>



Revision 23/09/15 Superseding  
issue of