

D7000

PREMIUM TURBO
DIESEL ENGINE OIL

MaxPro1 D7000 are premium turbo diesel engine oils specifically designed to lubricate a wide range of diesel and gasoline engines requiring API CI-4, SL or ACEA E7 performance lubricants. Formulated from premium hydrocracked base oils and latest additive packages to provide exceptional soot dispersancy, deposit control and wear protection. It can be used in all high performance four stroke diesel engines operating on low sulphur diesel fuel (<0.05 % mass) and under severe heavy duty conditions.

APPLICATIONS

MaxPro1 D7000 are recommended for use in European, North American and/or Japanese diesel engines which are turbocharged or naturally aspirated and operate under the most severe service conditions. Suitable for diesel and gasoline engines of old and new equipment; Commercial road transport, including the latest electronic controlled engines and those designed to meet Euro III emissions standards.

Also for Euro 4 and 5 compliant vehicles, except those units fitted with DPF (Diesel Particulate Filters) and requiring ACEA E6 or E9 oils.

FEATURES AND BENEFITS

- Provide effective control with respect to piston cleanliness and bore polishing
- Deliver excellent wear and turbocharger deposit control
- Exceptional oxidation stability and soot control extends oil drain capability
- Outstanding valve train wear protection maintains fuel economy.



Revision 23/09/15 Superseding
issue of

PERFORMANCE LEVEL

- API CI-4/CH-4/SL
- ACEA A3/B4
- ACEA E7
- Cummins CES 20072/7
- Detroit Diesel 93K215
- Mercedes-Benz 228.3
- MAN M 3275
- MTU OIL Category 2
- Volvo VDS-3
- Mack EO-M Plus

TYPICAL PHYSICAL CHARACTERISTICS

SAE grade	Test Method	10W-30	10W-40	15W-40	20W-50
Product Code		2060	2061	2062	2063
ASTM Colour	ASTM D1500	<3.0	<3.0	<3.0	<3.0
Density@ 15°C , kg/l	ASTM D1298	0.869	0.875	0.88	0.881
Viscosity, kinematic					
at 40°C , cSt	ASTM D445	79.0	98.9	111.8	170.5
at 100°C , cSt	ASTM D445	11.9	14.0	14.9	19.52
Viscosity Index	ASTM D2270	145	144	138	131
Flash point, COC, °C	ASTM D92	230	230	>230	>230
Pour point , °C	ASTM D97	-36	-36	-33	-21
TBN , mg KOH/g	ASTM D2890	9.2	9.2	9.2	9.2

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

Available Size & Part Number

	7L	20L	200L
D7000 SAE 10W-30		2060-20	2060-200
D7000 SAE 10W-40		2061-20	2061-200
D7000 SAE 15W-40	2062-07	2062-20	2062-200
D7000 SAE 20W-50		2063-20	2063-200



Revision 23/09/15 Superseding
issue of