

**MaxPro1 Super Racing 4T** is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of selected high performance, high viscosity index base stocks and a special proprietary additive package, to provide good engine cleanliness, good wear protection and corrosion protection.

**MaxPro1 Super Racing 4T** motorcycle oil is engineered to provide excellent oxidation resistance, as well as consistent viscosity.

**MaxPro1 Super Racing 4T** is recommended for lubrication when performance levels of **API SJ** and **JASO MA2** standards are required.

---

## APPLICATIONS

**MaxPro1 Super Racing 4T** is high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

---

## FEATURES AND BENEFITS

- Good wear protection
- Excellent thermal and oxidation stability
- Good corrosion protection.
- Improving fuel economy.

## SUPER RACING

HIGH PERFORMANCE  
MOTORCYCLE OIL



Revision 23/09/15 Superseding  
issue of

## PERFORMANCE LEVEL

It meets the performance requirements of:

- API SJ
- JASO MA2

## TYPICAL PHYSICAL CHARACTERISTICS

SAE grade	Test Method	20W-50
Product Code		<b>1509</b>
Appearance	VISUAL	B & C
ASTM Colour	ASTM D1500	L3.0
Density@ 15°C , kg/l	ASTM D1298	0.8725
Viscosity, kinematic		
at 40°C , cSt	ASTM D445	165.04
at 100°C , cSt	ASTM D445	19.94
Viscosity Index	ASTM D2270	140
Flash point, COC , °C	ASTM D92	240
Pour point , °C	ASTM D97	-21

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

## Available Size & Part Number

<b>SUPER RACING 4T</b>	<b>1L</b>
<b>SAE 20W-50</b>	<b>1509-01</b>

# SUPER RACING

HIGH PERFORMANCE  
MOTORCYCLE OIL



Revision 23/09/15 Superseding  
issue of