

MaxPro1 D3000 Monograde is a top tier universal mixed fleet oil for all turbo-charged and natural aspirated diesel engines from trucks, busses and machines working under moderate to severe conditions, for which extended drain periods are required.

MaxPro1 D3000 Monograde engine oils are formulated with high quality mineral base stocks and advanced additives technology to provide excellent wear protection, to minimize the formation of sludge and varnish, to protect against rust and bearing corrosion, and to resist foaming.

APPLICATIONS

Monograde 10W is recommended for hydraulic systems of civil engineering and construction equipment.

Monograde 30 is recommended for on-highway trucks, off-road construction and civil engineering equipment, light commercial diesel engines.

Monograde 40 is recommended for on-highway trucks, off-road construction, civil engineering and mining equipment, commercial vehicle diesel engines.

Monograde 50 is recommended for use in Fuller synchromesh gearboxes in commercial vehicles.

FEATURES AND BENEFITS

- Excellent engine deposit and sludge control
- Superior oxidation and oil thickening control
- Superb detergent-dispersant characteristics.
- Excellent anti-corrosion and anti-rust properties.
- Prolongs engine life and improves running efficiency

D3000

HIGH PERFORMANCE
HEAVY DUTY
DIESEL ENGINE OIL



Revision 23/09/15 Superseding
issue of

D3000

HIGH PERFORMANCE
HEAVY DUTY TURBO
DIESEL ENGINE OIL

PERFORMANCE LEVEL

It meets the performance requirements of:

- API CF / SF
- ACEA E2

TYPICAL PHYSICAL CHARACTERISTICS

SAE Grade	10W	30	40	50
Product Code	2074	2075	2076	2077
Specific Gravity @ 15°C	0.872	0.879	0.88	0.887
Color, ASTM D1500	L 2.5	L3.5	L4.0	L4.0
Flash Point (PMCC), °C	>194	>194	>205	>205
Pour Point, °C	-30	-12	-12	-12
Viscosity, Kinematic				
cSt @ 100°C	7.5	11	14.5	20
Viscosity Index	Min 100	Min 98	Min 98	Min 98
Total Base Number (TBN), ASTM D2896	7.5	8.1	8.1	8.1

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

Available Size & Part Number

	4L	5L	18L	200L
D3000 SAE 10W			2074-18	2074-200
D3000 SAE 30			2075-18	2075-200
D3000 SAE 40			2076-18	2076-200
D3000 SAE 50			2077-18	2077-200



Revision 23/09/15 Superseding
issue of