

MaxPro1 ATF is formulated with premium quality, synthetic blend base stocks combined with an advanced additive system, to address the multi vehicle needs of a universal Automatic Transmission fluid. Specially designed to deliver performance and maximum fuel efficiency for modern automatic transmissions. It is suitable for many transmissions manufactured by European, Asian and OEMs.

APPLICATIONS

MaxPro1 ATF is suitable for use in most GM and Ford applications, all Allison C4 applications, and any other application calling for use of DIIIH/M quality ATF.

PERFORMANCE LEVEL

It meets the performance requirements of:

- Dexron IIIH/M
- Allison C4

Not recommended for CVT, DCT or use in vehicles requiring Type F, MERCON® SP, Full Synthetic MERCON® , Nissan Matic K, Toyota/Lexus WS, Mercedes Benz 3403-M115, BMW 1375.4, or Volvo 1161540-8. Check owner's manual for exact specification.



Revision 23/09/15 Superseding
issue of

FEATURES AND BENEFITS

- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear, rust and corrosion
- Excellent low-temperature properties for easier shifting in cold weather
- Good seal compatibility
- Good foam resistance



TYPICAL PHYSICAL CHARACTERISTICS

		ATF
Product Code		3022
Test	Method	
Appearance	Visual	Red
Density @ 15°C, kg/l	ASTM D1298	0.852
Kinematic Viscosity,	ASTM D445	
@ 40°C, cSt		36.7
@ 100°C, cSt		7.03
Viscosity Index	ASTM D2270	156
Flash Point COC, °C	ASTM D92	205
Pour Point, °C	ASTM D97	-42
Brookfield Viscosity @ -40°C, cP	ASTM D2983	7500



The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development.

Available Size & Part Number

	1L	4L
MV ATF	3022-01	3022-04

Revision 23/09/15 Superseding
issue of